

"Petras, James" <James.Petras@m-e.aecom.

To GeneralPermits NPDES/R1/USEPA/US@EPA

cc Robert.Kubit@state.ma.us, "Moura, Stephanie" <Stephanie.Moura@mwra.state.ma.us>, Mark.Radville@mwra.state.ma.us, "Shreve, Betsy"

Subject Notice of Intent for NPDES Remediation General Permit

(RGR) - MWRA Pleasure Bay Stormwater Relocation Project

On behalf of the MWRA, attached please find an application for coverage under the RGP for a treated contaminated groundwater discharge associated with the construction of the Pleasure Bay Stormwater Relocation project in South Boston, MA.

A paper copy (to EPA and MA DEP) will follow in the mail early next week.

If you have any questions, please do not hesitate to call.

<<NOI for Coverage under RGP - MWRA Pleasure Bay.pdf>>

James Petras Senior Environmental Scientist METCALF & EDDY | AECOM 701 Edgewater Drive Wakefield, MA 01880

Phone: 781-224-6012 Fax: 781-224-5986 www.aecom.com www.m-e.com



NOI for Coverage under RGP - MWRA Pleasure Bay.pdf



Pleasure Bay Stormwater Relocation

Notice of Intent for NPDES Remediation General Permit for Construction Dewatering Activities

Prepared for:
Massachusetts Water Resources
Authority



Prepared by:



Submitted to:
MA Department of Environmental Protection
US Environmental Protection Agency

October 21, 2005



PARSONS BRINCKERHOFF QUADE & DOUGLAS, INC. AND METCALF & EDDY, INC., A JOINT VENTURE

701 EDGEWATER DRIVE, WAKEFIELD, MA 01880 TEL: 781-246-5200 • FAX: 781-224-5986

October 21, 2005

EPA New England RGP-NOC Processing Municipal Assistance Unit (CMU) 1 Congress Street, Suite 1100 Boston, MA 02114-2023

MA Department of Environmental Protection Division of Watershed Management 627 Main Street, 2nd Floor Worcester, MA 01608

Subject: MWRA Design Contract No. 6220

MWRA Construction Contract No. 7012 Pleasure Bay Stormwater Relocation

Remediation General Permit (RPG) for Construction Dewatering Activities

Dear EPA:

As you may recall, we submitted a request for a NPDES Exclusion for this project, on behalf of the Massachusetts Water Resources Authority (MWRA), in May 2005. In response, EPA granted NPDES Exclusion #MA-05I-072 on June 22, 2005. Since that time, MWRA has advertised the project for bid and selected a Contractor (the Dow Company). MWRA recently issued a Notice to Proceed (NTP) to the Contractor, who has begun mobilization. Although construction (and thus groundwater discharge) has not yet been initiated, it is expected to begin in the near future. In compliance with EPA's recent (September 15, 2005) letter announcing the availability of the Remediation General Permit, we are providing the enclosed Notice of Intent (NOI) seeking coverage under the RGP for dewatering activities associated with the Pleasure Bay Stormwater Relocation project (Attachment 1).

Since known groundwater contamination exists within and nearby the northwest portion of the proposed construction area, contaminated water may be encountered during dewatering activities in this location. In addition, several parameters listed in Appendix III of the RGP have been detected in monitoring wells installed along the Day Boulevard portion of the proposed pipeline route. However, based on the available groundwater data, with the exception of silver none of the detected parameters exceed the Appendix III effluent limitations.

The proposed project (the Pleasure Bay Stormwater Relocation), is a component of the MWRA's Long-Term CSO Control Plan for North Dorchester Bay and Reserved Channel (EOEA #10335, April 2004). The Pleasure Bay Stormwater Relocation project is being designed and constructed by the MWRA; however, the Massachusetts Department of Conservation and Recreation (DCR), which owns/manages the majority of the affected property, will be responsible for the long-term operation and maintenance of the pipeline.

The project entails diverting Pleasure Bay stormwater drainage away from the beach area and into the Reserved Channel requiring the construction of approximately 4,600 feet of new drain piping ranging from 18 to 48 inches. The locus map provided with the NOI identifies the entire project area (Attachment 1, Figure 1). The work would occur within streets or parkland managed

-		
-		

by DCR and the Massachusetts Port Authority (Massport), just south of Massport's Conley Terminal Facility. The new Pleasure Bay storm drains would run along Day Boulevard and Shore Road, and would connect into the existing BOS080 outfall just north of East 1st Street (Figure 1). In addition, to alleviate current flooding/ponding issues related to a failed drainage outfall, five catch basins collecting stormwater along the southern portion of Marine Park, in the vicinity of Kelly's Landing, will be connected by a proposed 24-inch diameter, 680-foot pipeline and rerouted to BOS 081, which discharges to North Dorchester Bay, in the short-term. This pipeline would later be incorporated into the near-surface stormwater piping to convey flows to the proposed North Dorchester Bay Storage Tunnel, which is currently in design.

The storm drains will be constructed by cut-and-cover excavation at a depth ranging from approximately 6 to 15 feet below ground surface. Existing catch basins will be removed and replaced with deep sump catch basins, each having a minimum sump of 4 feet. Existing laterals will be replaced, and oil trap hoods will be installed on all new lateral outlets. To comply with the latest MA DEP guidelines for stormwater management, an offline particle separator will also be provided for the treatment of relocated stormwater discharge to the Reserved Channel.

Based on historic land uses in and near the northwest portion of the project area, the potential exists for some of the MWRA construction dewatering activities to encounter contaminated groundwater. Considerable data from subsurface sampling wells (Attachment 1, Figure 2), associated with remedial investigations conducted by others, were reviewed. The anticipated chemical constituents and concentrations of the contaminants within the groundwater in this area are provided in Section 3.0 of the NOI. The analytical data used to develop this section of the NOI are provided in Attachment 2. The anticipated dewatering activities and the type of treatment proposed are described in the NOI (Section 4.0). The Contractor will not be permitted to cause groundwater drawdown outside the excavation, so as not to exacerbate any existing groundwater contamination plume or adversely impact any operating off-site groundwater treatment system.

For most of the length of the new pipelines, the excavation/trenching will be shallow, and thus it will be unlikely that groundwater will be encountered. However, construction of the deeper portions of the pipeline alignment, as well as the construction of the off-line particle separator and connection to BOS080, is anticipated to encounter groundwater. In these locations, in order to safely construct the pipeline, it is anticipated that groundwater will be pumped from the trench. As described in the NOI (Section 5.0), groundwater from the excavation and trench will be discharged to a mobile treatment train consisting of an oil/water separator and a GAC filter. Based on proximity to the dewatering activity, treated water will then be discharged to either BOS080 or one of 13 Pleasure Bay outlets (Attachment 1, Figure 3).

If you have any questions or require additional information relative to this NOI, please contact Stephanie Moura at the MWRA (617-788-4399) or me (781-224-6172).

Sincerely.

Betsy Shreve-Gibb Project Manager

> cc: S. Moura (MWRA) B. Kubit (MA DEP)

ATTACHMENT 1
NOTICE OF INTENT

B. Suggested Form for Notice of Intent (NOI) for the Remediation General Permit

1. General site information. Please provide the following information about the site: a) Name of facility/site: Facility/site address: Pleasure Bay Stormwater Relocation Project Shore Road and Farragut Road; and the eastern terminus of Day Boulevard South Boston, MA 02127 Location of facility/site: Facility SIC code(s): Street: longitude: <u>71°1'18.88</u> latitude: <u>42°20'15.10</u> b) Name of facility/site owner: Massachusetts Water Resources Authority Town: Boston Email address of owner: State: Zip: County: 02129 Suffolk stephanie.moura@mwra.state.ma.us MA Telephone no. of facility/site owner: (617) 788-4399 ___ 2. State/Tribal_ Fax no. of facility/site owner: (617) 788-4888 Owner is (check one): 1. Federal_ 3. Private_____ 4. other, if so, describe: Address of owner (if different from site): Street: 100 First Avenue, Charlestown Navy Yard, Building 39 State: MA Town: Boston Zip: ₀₂₁₂₉ County: Suffolk Operator telephone no: (617) 788-4399 c) Legal name of operator:

Remediation General Permit - Notice of Intent

Operator contact name and title: Stephanie Moura, Project Manager

Massachusetts Water Resources Authority


Operator fax no.: (617) 788-4888

Operator email:

stephanie.moura@mwra.state.ma.us

Address of operator (if different fi	rom owner):	Street:										
Town:		State:	Zip:	County:								
 Has a prior NPDES permit exclu Has a prior NPDES application (d) Check "yes" or "no" for the following: 1. Has a prior NPDES permit exclusion been granted for the discharge? Yes No, if "yes," number: MA-05I-072 2. Has a prior NPDES application (Form 1 & 2C) ever been filed for the discharge? Yes No, if "yes," date and tracking #: 3. Is the discharge a "new discharge" as defined by 40 CFR 122.2? Yes No 4. For sites in Massachusetts, is the discharge covered under the MA Contingency Plan (MCP) and exempt from state permitting? Yes No											
e) Is site/facility subject to any State permitting or other action which is causing the generation of discharge? Yes No \(\bullet \) [1] Is the site/facility covered by any other EPA permit, including: 1. multi-sector storm water general permit? Y N \(\bullet \), if Y, number: 2. phase I or II construction storm water general permit? Y N , if Y, number: 3. state agency contact information: name, location, and telephone number: 4. any other water quality related permit? Y N \(\bullet \), if Y, number:												
2. Discharge information. Pleas	se provide information about the di	ischarge, (attachi	ng additional sheets as need	ed) including:								
a) Describe the discharge activities Dewatering associated with exce	for which the owner/applicant is savation of trenches for construction	•		cle separator.								
b) Provide the following information about each discharge: 1) Number of discharge points: 14	2) What is the maximum and av Average flow TBD Is ma For average flow, include the uni	ximum flow a de	esign value? Y N	er second, ft ³ /s)? Max. flow 0.9 design value or estimate if not available.								
3) Latitude and longitude of each d	ischarge within 100 feet:	·										
PB-1: Lat 71° 0' 52.51" W Long 42° 20' 17.83" N PB-2: Lat 71° 0' 53.06" W Long 42° 20' 18.48" N PB-3: Lat 71° 0' 56.84" W Long 42° 20' 18.94" N PB-4: Lat 71° 1' 0.87" W Long 42° 20' 19.00" N PB-5: Lat 71° 1' 4.68" W Long 42° 20' 18.76" N PB-6: Lat 71° 1' 8.52" W Long 42° 20' 18.57" N PB-7: Lat 71° 1' 12.16" W Long 42° 20' 18.06" N PB-8: Lat 71° 1' 15.80" W Long 42° 20' 16.94" N PB-9: Lat 71° 1' 18.88" W Long 42° 20' 12.86" N PB-10 Lat 71° 1' 20.82" W Long 42° 20' 12.86" N PB-11 Lat 71° 1' 24.24" W Long 42° 20' 6.16" N PB-12 Lat 71° 1' 22.83" W Long 42° 20' 3.86" N PB-13 Lat 71° 1' 20.77" W Long 42° 20' 1.29" N PB-7: Lat 71° 1' 12.16" W Long 42° 20' 18.06" N PB-8: Lat 71° 1' 15.80" W Long 42° 20' 15.10" N PB-9: Lat 71° 1' 20.82" W Long 42° 20' 12.86" N PB-13 Lat 71° 1' 20.77" W Long 42° 20' 1.29" N PB-13 Lat 71° 1' 31.12" W Long 42° 20' 29.56" N												

4) If hydrostatic testing, total volume of the discharge (gals): N/A	5) Is the discharge intermittent vor seasonal ? Is discharge ongoing Yes No vor ?
c) Expected dates of discharge (mm/dd/yy): start 10/28/05	end 04/30/06
d) Please attach a line drawing or flow schematic showing water 1. sources of intake water, 2. contributing flow from the operation	flow through the facility including: n, 3. treatment units, and 4. discharge points and receiving waters(s).



3. Contaminant information. In order to complete this section, the applicant will need to take a minimum of one sample of the untreated water and have it analyzed for all of the parameters listed in Appendix III. Historical data, (i.e., data taken no more than 2 years prior to the effective date of the permit) may be used if obtained pursuant to: i. Massachusetts' regulations 310 CMR 40.0000, the Massachusetts Contingency Plan ("Chapter 21E"); ii. New Hampshire's Title 50 RSA 485-A: Water Pollution and Waste Disposal or Title 50 RSA 485-C: Groundwater Protection Act; or iii. an EPA permit exclusion letter issued pursuant to 40 CFR 122.3, provided the data was analyzed with test methods that meet the requirements of this permit. Otherwise, a new sample shall be taken and analyzed.

a) Based on the analysis of the sample(s) of the untreated influent, the applicant must check the box of the sub-categories that the potential discharge falls within.

Gasoline Only	VOC Only	Primarily Metals	Urban Fill Sites 🗸	Contaminated Sumps	Mixed Contaminants	Aquifer Testing
Fuel Oils (and Other Oils) only	VOC with Other Contaminants	Petroleum with Other Contaminants	Listed Contaminated Sites	Contaminated Dredge Condensates	Hydrostatic Testing of Pipelines/Tanks	Well Development or Rehabilitation

b) Based on the analysis of the untreated influent, the applicant must indicate whether each listed chemical is **believed present** or **believed absent** in the potential discharge. Attach additional sheets as needed.

PARAMETER	Believe Absent	Believe Present	# of Samples	Type of Sample	Analytical Method	Minimum Level (ML) of	Maximum daily	value	Avg. daily value	e
			(1 min- imum)	(e.g., grab)	Used (method #)	Test Method	concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
1. Total Suspended Solids		V.								
2. Total Residual Chlorine										
3. Total Petroleum Hydrocarbons		•	3	grab	EPH by MADEP Method 1.0	110 ug/l	594 (a)	1.30E+0	384	8.37E-1
4. Cyanide										
5. Benzene	~									
6. Toluene	V									
7. Ethylbenzene	V					·				
8. (m,p,o) Xylenes	V									
9. Total BTEX4	V									

⁴BTEX = Sum of Benzene, Toluene, Ethylbenzene, total Xylenes.

a.) OW98-359

PARAMETER	Believe Absent	Believe Present	# of Samples	Type of Sample (e.g.,	Analytical Method	Minimum Level (ML) of	Maximum daily	value	Avg. daily valu	e
			(1 min- imum)	grab)	Used (method #)	Test Method	concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
10. Ethylene Dibromide (1,2- Dibromo-methane)										
11. Methyl-tert-Butyl Ether (MtBE)		V	4	grab	VPH by MADEP Method 1.0	2 ug/l	2.5 (b)	5.45E-3	1.4	3.05E-3
12. tert-Butyl Alcohol (TBA)										
13. tert-Amyl Methyl Ether (TAME)										
14. Naphthalene	~									
15. Carbon Tetra- chloride	~									
16. 1,4 Dichlorobenzene	~									
17. 1,2 Dichlorobenzene	~									
18. 1,3 Dichlorobenzene	~				-					
19. 1,1 Dichloroethane	~								-	
20. 1,2 Dichloroethane	~				-					
21. 1,1 Dichloroethylene										
22. cis-1,2 Dichloro- ethylene										
23. Dichloromethane (Methylene Chloride)	V									
24. Tetrachloroethylene										

b.) M&E-5

PARAMETER	Believe Absent	Believe Present	# of Samples	Type of Sample (e.g.,	Analytical Method Used	ed (ML) of Test	Maximum daily v	alue	Avg. daily Valu	e
			(1 min- imum)	grab)	(method #)	Method	concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
25. 1,1,1 Trichloroethane	V					- ""				
26. 1,1,2 Trichloroethane	~									
27. Trichloroethylene										
28. Vinyl Chloride	~									
29. Acetone										
30. 1,4 Dioxane										
31. Total Phenols								ļ		
32. Pentachlorophenol		<i>.</i>								
33. Total Phthalates ⁵ (Phthalate esthers)										
34. Bis (2-Ethylhexyl) Phthalate [Di- (ethylhexyl) Phthalate]										
35. Total Group I Polycyclic Aromatic Hydrocarbons (PAH)										
a. Benzo(a) Anthracene	~									
b. Benzo(a) Pyrene	V									
c. Benzo(b)Fluoranthene	~									
d. Benzo(k) Fluoranthene	~									
e. Chrysene	~									

⁵The sum of individual phthalate compounds.

PARAMETER	Believe Absent	Believe Present	# of Samples	Type of Sample (e.g.,	Analytical Method Used	Minimum Level (ML) of	Maximum daily	value	Average daily v	alue/
			(1 min- imum)	grab)	(method #)	Test Method	concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
f. Dibenzo(a,h) anthracene	•									
g. Indeno(1,2,3-cd) Pyrene	~									
36. Total Group II Polycyclic Aromatic Hydrocarbons (PAH)						·				
h. Acenaphthene	~									
i. Acenaphthylene	~									
j. Anthracene	~									
k. Benzo(ghi) Perylene	~									
l. Fluoranthene		~	4	grab	MADEP Method 1.0	l.l ug/l	5.2 (c)	1.13E-2	1.7	3.71E-3
m. Fluorene	/									
n. Naphthalene-		~	4	grab	MADEP Method 1.0	2.0 ug/l	10.7 (c)	2.33E-2	3.4	7.41E-3
o. Phenanthrene		~	4	grab	MADEP Method 1.0	1.1 ug/l	5.2 (c)	1.13E-2	1.7	3.71E-3
p. Pyrene		~	4	grab	MADEP Method 1.0	1.1 ug/l	5.5 (c)	1.20E-2	1.8	3.93E-3
37. Total Polychlorinated Biphenyls (PCBs)										
38. Antimony	~									
39. Arsenic		V	3	grab	SW-846 6000/7000	2.4 ug/l	13.0 (a)	2.83E-2	5.1	1.11E-2
40. Cadmium		~	3	gтab	SW-846 6000/7000	2.2 ug/l	3.2 (a)	6.98E-3	1.8	3.93E-3
41. Chromium III										
42. Chromium VI										

c.) M&E-319

PARAMETER	Believe Absent	Believe Present	# of Samples	Type of Sample (e.g.,	Analytical Method	od Level (ML) of Test Method	Maximum daily	value	Avg. daily value	
			(1 min- imum)	grab)	Used (method #)		concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
43. Copper	V									
44. Lead	~									
45. Mercury	~						1			
46. Nickel		V	3	grab	SW-846 6000/7000	8.5 ug/L	8.6 (d)	1.88E-2	8.6	1.88E-2
47. Selenium	~									
48. Silver		V	3	grab	SW-846 6000/7000	3.6 ug/l	3.6 (d)	7.85E-3	3.6	7.85E-3
49. Zinc	V									
50. Iron										
Other (describe):										

Step 1: Do any of the metals in the influent have a reasonable potential to exceed the effluent limits in Appendix III (i.e., the limits set at zero to five dilutions)? Y _ V _ N	If yes, which metals? Ni and Ag. However, the proposed discharges are to saltwater (Reserved Channel and Pleasure Bay)
Step 2: For any metals which have reasonable potential to exceed the Appendix III limits, calculate the dilution factor (DF) using the formula in Part I.A.3.c) (step 2) of the NOI instructions or as determined by the State prior to the submission of this NOI. What is the dilution factor for applicable metals?	Look up the limit calculated at the corresponding dilution factor in Appendix IV. Do any of the metals in the influent have the potential to exceed the corresponding effluent limits in Appendix IV (i.e., is the influent concentration above the limit set at the calculated dilution

Y___N__ If "Yes," list which metals:

d.) OW98-365

DF: ____

Metals:_

Remediation General Permit - Notice of Intent

c) For discharges where metals are believed present, please fill out the following:

4. Treatment system informa	ation. Please desc	ribe the treatmen	it system using separ	rate sheets as necessar	ry, including:		
a) A description of the treatm	nent system, inclu	ding a schematic	of the proposed or e	xisting treatment syst	em:		
The system will entail a come EPA.	ercially-manufact	ured portable oil/	water separator and	a GAC filter system of	capable of producing a	a effluent within limi	ts established by
b) Identify each applicable treatment unit (check all that apply):	Frac. tank	Air stripper	Oil/water sep	parator 🗸	Equalization tanks	Bag filter	GAC filter
	Chlorination	Dechlorination	n Other (please	e describe):			
c) Proposed average and ma Average flow rate of discharg			nute) for the dischargate of treatment syste		w rate(s) (gallons per n esign flow rate of treatn		nt system:
d) A description of chemical N/A	additives being us	sed or planned to	be used (attach MSI	OS sheets):			
5. Receiving surface water(s)	. Please provide i	information abou	t the receiving water	(s), using separate sh	eets as necessary:		
a) Identify the discharge path	i i	Direct	Within facility	Storm drain_	River/brook	Wetlands	Other (describe): Pleasure Bay and Reserved Channel
b) Provide a narrative descrip	otion of the discha	rge pathway, inc	luding the name(s) o	f the receiving waters	 3:		
Groundwater from the excava Treated water will then be dis	ation/trenching ass scharged to one Cf	sociated with the SO outfall, or one	proposed 4,600 feet e of 13 outlets, based	(approx.) of new drain a new drain a new drain to the control of t	in piping will be discha excavation.	irged to a mobile trea	tment train.

 c) Attach a detailed map(s) indicating the site location and location of the outfall to the receiving water: 1. For multiple discharges, number the discharges sequentially. 2. For indirect dischargers, indicate the location of the discharge to the indirect conveyance and the discharge to surface water The map should also include the location and distance to the nearest sanitary sewer as well as the locus of nearby sensitive receptors (based on USGS topographical mapping), such as surface waters, drinking water supplies, and wetland areas.
d) Provide the state water quality classification of the receiving water Reserved Ch SBCSO; Pleasure Bay SB,
e) Provide the reported or calculated seven day-ten year low flow (7Q10) of the receiving watercfs Please attach any calculation sheets used to support stream flow and dilution calculations.
f) Is the receiving water a listed 303(d) water quality impaired or limited water? Yes No If yes, for which pollutant(s)? Is there a TMDL? Yes No No If yes, for which pollutant(s)?
6. Results of Consultation with Federal Services: Please provide the following information according to requirements of Part I.B.4 and Appendices II and VII.
a) Are any listed threatened or endangered species, or designated critical habitat, in proximity to the discharge? YesNo Has any consultation with the federal services been completed? Yes
b) Are any historic properties listed or eligible for listing on the National Register of Historic Places located on the facility or site or in proximity to the discharge? Yes No Have any state or tribal historic preservation officer been consulted in this determination (Massachusetts only)? Yes No

7. Supplemental information. :		
Please provide any supplemental information.	Attach any analytical data used to support the application.	Attach any certification(s) required by the general permit.
Attachment 1: NOI and Figures 1, 2, and 3		
Attachment 2: Analytical Data		
	•	
		•
·		

Facility/Site Name: Pleasure Bay Stormwooder Relocation

Operator signature: Adyl M Wallock
Title: Director, C50 Program/Energy

Date: October 21, 2005



Enter your transmittal number

W 069822

Transmittal Number

10. Ext. #

Your unique Transmittal Number can be accessed online: http://www.mass.gov/dep/counter/trasmfrm.shtml or call DEP's InfoLine at 617-338-2255 or 800-462-0444 (from 508, 781, and 978 area codes).

Massachusetts Department of Environmental Protection

Transmittal Form for Permit Application and Payment

1. Please type or print. A separate Transmittal Form must be completed for each permit application.

2. Make your check payable to the Commonwealth of Massachusetts and mail it with a copy of this form to: DEP, P.O. Box 4062, Boston, MA

3. Three copies of this form will be needed.

Copy 1 - the original must accompany your Copy 2 must accompany your fee payment. Copy 3 should be retained for your records

4. Both fee-paying and exempt applicants must mail a copy of this transmittal form to:

> P.O. Box 4062 Boston, MA 02211

* Note: For BWSC Permits. enter the LSP.

A. Permi	t Intorma	tion
4. Permi	t Intorma	tion

BRP WM 12 Remediation General Permit – Construction Dewatering 1. Permit Code: 7 or 8 character code from permit instructions 2. Name of Permit Category Construction Dewatering: Pipeline – Installation of approximately 4,600 feet of new drain piping ranging from 18 to 48 inches. Known groundwater contamination, from urban fill, as well as a petroleum spill, exists within portions of the construction area which will require dewatering. 3. Type of Project or Activity

B. Applicant Information – Firm or Individual Massachusetts Water Resources Authority 1. Name of Firm - Or, if party needing this approval is an individual enter name below:

100 First Avenue, Charlestown Navy Yard, Building 39

5. Street Address Boston 02129 617-788-4399 6. City/Town 7. State 8. Zip Code 9. Telephone # c/o Stephanie Moura stephanie.moura@mwra.state.ma.us

11. Contact Person 12. e-mail address (optional)

permit application. C. Facility, Site or Individual Requiring Approval Pleasure Bay Stormwater Relocation Project 1. Name of Facility, Site Or Individual Primarily within eastern terminus of Day Boulevard and Shore Road 2. Street Address **Boston** 02127 3. City/Town 5. Zip Code 7. Ext. # 4. State 6. Telephone # 8. DEP Facility Number (if Known) 9. Federal I.D. Number (if Known) 10. BWSC Tracking # (if Known)

D. Application Prepared by (if different from Section B)*

Metcalf & Eddy 1. Name of Firm Or Individual 701 Edgewater Drive 2. Address Wakefield MA 781-224-6172 3. City/Town 5. Zip Code 4 State 7. Ext. # c/o Betsy Shreve-Gibb 8. Contact Person 9. LSP Number (BWSC Permits only)

E. Permit - Project Coordination

1. Is this project subject to MEPA review?

✓ yes ☐ no If yes, enter the project's EOEA file number - assigned when an Environmental Notification Form is submitted to the MEPA unit:

10335 (Certificate issued 7/16/04) EOEA File Number

F. Amount Due

DEP Use Only

Special Provisions:

Permit No: There are no fee exemptions for BWSC permits, regardless of applicant status.

☐ Hardship Request - payment extensions according to 310 CMR 4.04(3)(c).


☐ Alternative Schedule Project (according to 310 CMR 4.05 and 4.10). Rec'd Date:

Homeowner (according to 310 CMR 4.02).

Reviewer: Check Number


Dollar Amount Date

tr-formw.doc • rev. 11/04 Page 1 of 1









ATTACHMENT 2 ANALYTICAL DATA

TABLE D-13
DETECTED CONCENTRATIONS IN GROUNDWATER SAMPLES
SUPPLEMENTAL EXPLORATION PROGRAM: PLEASURE BAY STORM DRAIN

	WELL ID:			OW98-359	OW98-362	I OV	V98-365
	WELL LOCATION:	REPORTABLE	FEDERAL	Pleasure Bay	Pleasure Bay	Pies	sure Bav
)	WEEL 2007/110111			1 1000010 009	, icaseic suy	''~	Du,
1		CONCENTRATIONS	SDWA		į.		l l
	SAMPLE DELIVERY GROUP:	GW2 (1)	MCLs (2)	S49	\$49	1	S49
	SHEET NUMBER:	``			ł	1	- 1
					1	1	ı
	BORING TYPE:				1	1	,
	SCREENED INTERVAL (FT BGS):			5 - 15	0.5 - 17.5	1 :	5-15 [
	SAMPLING DATE:			11/18/99	11/16/99	4.	1/16/99
	MCP REPORTING CATEGORY:		en e	GW2	GW2		GW2
						I	
	VOLATILE ORGANICS (µg/L)			None Detected	None Detected	None	Detected
	" - '						
	1/01 ATH C DETOOL CHILLING DOOL DOON (- 0)						1
	VOLATILE PETROLEUM HYDROCARBONS (µg/L)			Ì	ŀ	ŀ	1
	C5-C8 Allphatics (excludes BTEX and MTBE)	1,000	NL	< 100	< 100	<	100
	C9-C12 Aliohatics	1.000	NL	< 25	l < 25	<	25
	C9-C10 Aromatics	4.000	NL	< 25	< 25	-	25
		4,000	NL	< 25	< 25	\ \ \	25
	Targeted VPH Analytes:			ł			
	Methyl-tert-butyl ether (MTBE)	50.000	NL	< 2	< 2	۱ <	2
	Benzene	2.000	5	< 2	< 2	<	2
	Toluene	6,000	1,000	< 2	< 2	<	2
	Ethylbenzene	4,000	700	< 2	< 2	<	2
	m-&p-Xylenes	•		< 2	< 2	-	2
		0.000	40.000			•	
	o-Xylene	6,000	10,000	< 2	< 2	<	2
	Naphthalene	6,000	NL	< 2	< 2	<	2
				ĺ	Į.	ı	1
	EXTRACTABLE PETROLEUM HYDROCARBONS (µg/L)				1	١.	i
		1.000	NL	J 210	< 110	١ ,	110
	C9-C18 Aliphatics				1	\ \ \ \	
	C19-C36 Aliphatics	20,000	NL	180	< 110	ı	190
	C10-C22 Aromatics (excludes Targeted PAH Analytes)	30,000	NL	300	< 110	1	130
	Targeted PAH Analytes:				''-	1	
					l	1	
	Acenaphthene	5,000	NL	< 1.1	< 1.1	 <	1:1
	Acenaphthylene	3,000	NL	< 1.1	< 1.1	۱ <	1.1
	Anthracene	600	NL	< 1.1	< 1.1	<	1.1
	Benzo(a)anthracene	3,000	NL	< 1.1	< 1.1	<	1.1
	Benzo(a)pyrene	3,000	0.2	< 1.1	< 1.1	<	1.1
	Benzo(b)fluoranthene	3,000	NiL	< 1.1	l < 1.1	۱ <	1.1
	Benzo(g,h,i)perylene		NL	< 1.1	< 1.1	-	
		3,000			,	1	1.1
	Benzo(k)fluoranthene	3,000	NL	< 1.1	< 1.1	<	1.1
	Chrysene	3,000	NL	< 1.1	< 1.1	 <	1.1
	Dibenz(a,h)anthracene	3.000	NL.	< 1.1	< 1.1	<	1.1
				***	1	5	
-	Fluoranthene	200	NL.	< 1.1	< 1.1	 <	1.1
i	Fluorene	3,000	NL	< 1.1	< 1.1	 <	1.1
	Indeno(1,2,3-c,d)pyrene	3,000	NL	< 1,1	< 1.1	<	ii
	Naphthalene	6,000	·NL	< 1.1	< 1.1	<	1.1
	Phenanthrene	50	NL	< 1.1	< 1.1	<	1.1
	Pyrene	3.000	NL	< 1.1	< 1.1	<	1.1
	2-Methylnaphthalene	3,000	NL	< 1.1	< 1.1	-	1.1
	moory map in larene	3,000	NL	~ 1.1	1.1	١ `	1,1
		İ		1	i .	1	
	DISSOLVED PRIORITY POLLUTANT METALS			Y	1	Į	
	PLUS BARIUM, IRON, AND MANGANESE (7) (µg/L)				I	I	1
	Antimony	300		- 00		١	1
			6	< 2.0	< 2,0	<	2.0
- 1	Arsenic	400	50	13.02	< 2.4	<	2.4
1	Barlum	30,000	2,000	131	182	l	88.4
- 1	Beryllum	50	•	< 0.40	< 0.30	<	0.30
ı			4		1	ı	
ı	Cadmium	10	5	3.2	<j 2.2<="" td=""><td><!--</td--><td>2.2</td></td></j>	</td <td>2.2</td>	2.2
. !	Chromium	2,000	100	< 7.8	< 3.3	<	3.3
ı	Copper	100,000	1,300 (5)	< 6.2	< 6.2	<	6.2
,	rr-·	100,000	1,500 (5)	- 0.2	1 0.2	1 `	J.2

TABLE D-13 DETECTED CONCENTRATIONS IN GROUNDWATER SAMPLES SUPPLEMENTAL EXPLORATION PROGRAM: PLEASURE BAY STORM DRAIN

SUFFICIENT AL EXPLORATION PROGRAM. PLEASURE									
	WELL ID:			0	W98-359	1	W98-382		OW98-365
	WELL LOCATION:	REPORTABLE CONCENTRATIONS	FEDERAL SDWA	Pie	asure Bay	Pk	easure Bay	P	leasure Bay
	SAMPLE DELIVERY GROUP:	GW2 (1)	MCLs (2)		S49	1	S49	1	S49
	SHEET NUMBER:	''	٠.	1		1		1	
	BORING TYPE:	1				1		ı	
ł	SCREENED INTERVAL (FT BGS):				5 - 15	1 (0.5 - 17.5	1	5 - 15
	SAMPLING DATE:	1		1	11/16/99	1	11/16/99	[11/16/99
	MCP REPORTING CATEGORY:	<u> </u>		1_	GW2		GW2	1	GW2
Iron		NL	300 (4)	T	NA	1	NA		NA
Lead		30	15	إدا ا	0.84	ব	0.84	إحا	0.84
Manganese		NL	50 (4)		NA	1	NA	1	NA
Mercury		1	2	<	0.10	<	0.10	<	0.10
Nickel		80	NL	<	8.5	<	8.5	1	8.6
Selenium		80	50	⊲	1.8	<	1.8	احا	9.0
Silver		7	100 (4)	<	3.5	<	3.5	1	3.6
Thallium		400	2	<j< td=""><td>1.5</td><td>حا ا</td><td>1.5</td><td><j< td=""><td>7.5</td></j<></td></j<>	1.5	حا ا	1.5	<j< td=""><td>7.5</td></j<>	7.5
Zinc		900	5,000 (4)	<	28.0	<	28.0	<	28.0
			1,	1		1		,	

NOTES:

- NOTES:

 (1) Reportable Concentrations are from the MCP (MADEP, 1995 and revisions through 10/31/97).

 (2) Federal Safe Drinking Water Act Maximum Contaminant Levels. These values are included as an aid in evaluating the need for treatment of water generated from dewatering of excavations, prior to discharge to surface water. Such discharges are regulated under the National Pollutant Discharge Etimination System (NPDES). Although their use is not codified in regulation or specifically stated in policy, MCLs are generally used by EPA when stating NPDES permit limits for discharge to a water body.

 (3) MCL is for total thalomethanes.

 (4) MCL for chloride, iron, manganese, silver, sulfate, total dissolved solids, and zinc is a secondary MCL (non-enforceable and established for aesthetic reasons).

 (5) Treatment technique. 90% of tap samples must meet this "no action" level for copper.

 (6) Samples were collected by EPA low-flow method and were NOT filtered in the field or in the faboratory before analysis.

 (7) Samples were collected by EPA low-flow method and were NOT filtered before being bottled, preserved and submitted to the laboratory for analysis.

 The analyte was not detected at this concentration; value presented is the sample detection limit.

 Value is approximate due to limitations identified in the quality control review.

 R Value rejected due to limitations identified in the quality control review.

 No Not Analyzed or Not Applicable.

 No Reading due to instrument maifunction

 No Reading due to instrument maifunction

 2,000 Concentration exceeds the GWZ reportable concentration.

 Concentration exceeds the federal SDWA MCL.



LABORATORY REPORT **VOLATILE ORGANIC COMPOUNDS-EPA METHOD 8260B**

Client: Metcalf & Eddy

Client I.D.: MWRA Contract No. 6220 North Dorchester Bay/CSO

98-359

AMRO I.D.: 24809-02

Date sampled: 11/16/99

Date Received: 11/17/99 Date Analyzed: 11/18/99

Date prepared: 11/18/99 Sample Qty/Type: 1/Water

Test <u>Parameter</u>	Results (ug/L)	Reporting <u>Limit (ug/L)</u>
Chloromethane	ND	5.0
Bromomethane	ND	2.0
Vinyl Chloride	ND	2.0
Dichlorodifluoromethane	ND	5.0
Chloroethane	ND	5.0
Methylene Chloride	ND	5.0
Trichlorofluoromethane	ND	2.0
1,1-Dichloroethene	ND	1.0
Bromochloromethane	ND	2.0
1,1-Dichloroethane	ND	2.0
cis-1,2-Dichloroethene	ND	2.0
trans-1,2-Dichloroethene	ND	2.0
Chloroform	ND	2.0
Dibromomethane	ND	2.0
1,2-Dichloroethane	ND	2.0
2,2-Dichloropropane	ND	2.0
1,1,1-Trichloroethane	ND	2.0
Carbon Tetrachloride	ND	2.0
Bromodichloromethane	ND	2.0
1,2-Dichloropropane	ND	2.0
1,1-Dichloropropene	ND	2.0
Trichloroethene	ND	2.0
Dibromochloromethane	ND	2.0
1,1,2-Trichloroethane	ND	2.0
Benzene	ND	2.0
1,3-Dichloropropane	ND	2.0
Bromoform	ND	2.0
1,1,1,2-Tetrachloroethane	ND	2.0
Tetrachloroethene	ND	2.0
1,2-Dibromoethane	ND	2.0
1,1,2,2-Tetrachloroethane	ND	2.0
Toluene	ND	2.0
Chlorobenzene	ND	2.0
Ethylbenzene	ND	2.0
Bromobenzene	ND	2.0
Isopropylbenzene	ND	2.0
Styrene	ND	2.0
n-Propylbenzene	ND	2.0
	NU	2.0

Cont. next page



LABORATORY REPORT VOLATILE ORGANIC COMPOUNDS-EPA METHOD 8260B

Client: Metcalf & Eddy

Client I.D.: 98-359 AMRO I.D.: 24809-02

Test <u>Parameter</u>	Results (ug/L)	Reporting <u>Limit (ug/L)</u>
cis-1,3-Dichloropropene	ND	1.0
trans-1,3-Dichloropropene	ND	1.0
Xylene (total)	ND	2.0
1,2-Dibromo-3-chloropropane	ND	5.0
tert-Butylbenzene	ND	2.0
2-Chlorotoluene	ND	2.0
Hexachlorobutadiene	ND	2.0
4-Chlorotoluene	ND	2.0
sec-Butylbenzene	ND	2.0
1,3-Dichlorobenzene	ND	2.0
1,2-Dichlorobenzene	ND	2.0
1,4-Dichlorobenzene	ND	2.0
1,2,3-Trichloropropane	ND	2.0
n-Butylbenzene	ND	2.0
4-Isopropyitoluene	ND	2.0
Naphthalene	ND	2.0
1,2,4-Trimethylbenzene	ND	2.0
1,3,5-Trimethylbenzene	ND	2.0
1,2,3-Trichlorobenzene	ND	2.0
1,2,4-Trichlorobenzene	ND	2.0
Methyl-tert-butyl ether (MTBE)	ND	2.0

ND = Not Detected at or above the reporting limit.

The Reporting Limit is defined as the lowest concentration the laboratory can accurately quantitate.

Analyzed By: JSL

Page 2 of 2

TABLE 1. DETECTED CONCENTRATION IN GROUNDWATER SAMPLES FROM THE NORTHWEST PORTION OF THE PLEASURE BAY STORMWATER RELOCATION PROJECT

WELL ID:	AMB-208	AMB-209	AMB-210	M&E-4	M&E-5	M&E-319
WELL LOCATION:	Pleasure Bay					
/OLATILE PETROLEUM HYDROCARBONS (μg/L)				ı		
C5-C8 Aliphatics (excludes BTEX and MTBE)	nd	nd	nd	nd	nd	nd
C9-C12 Aliphatics	nd	nd	nd	nd	nd	nd
9-C10 Aromatics	nd	nd	nd	nd	nd	nd
argeted VPH Analytes:	nd	nd	nd	nd	nd	nd
Methyl-tert-butyl ether (MTBE)	nd	nd	nd	nd	2.5	nd nd
Benzene	nd	nd	nd	nd	nd	nd
Toluene	nd	nd	nd	nd	nd	nd
Ethylbenzene	nd	nd	nd	nd	nd	nd
m-&p-Xylenes	nd	nd	nd			
o-Xylene	nď	nd	nd			-
Naphthalene	nd	nd	nd	nd	nd	10.7
PH and Target PAH Analytes (μg/L)						
9-C18 Aliphatics	l nd i	nd	nd	nd	nd	nd
19-C36 Aliphatics	nd	nd	nd	nď	nd	nd
11-C22 Aromatics (excludes Targeted PAH Analytes)	nd	nd	270	nď	nd	185
cenaphthene	nd	nd	nd	nd	nd	nd
cenaphthylene	nd	nd	nd	nd	nd nd	nd
nthracene	nd	nd	nd	nd	nd	nd
enzo(a)anthracene	nd	nd l	nd	nd	nd	nd
enzo(a)pyrene	nd	nd	nd	nd	nd	nd
enzo(b)fluoranthene	nd	nd	nd	nd	nď	nd
enzo(g,h,i)perylene	nd	nd	nd	nd	nd	nd
enzo(k)fluoranthene	nd	nd	nd	nd	nd	nd
hrysene	nd	nd	nd	nd	nd	nd
ibenzo(a,h)anthracene	nd	nd	nd	nd	nd	nd
luoranthene	nd	nd	nd	nd	nd	5.2
luorene	nd	nd	nd	nd	nd	nd
deno(1,2,3-c,d)pyrene	nd	nd	nd	nd	nd	nd
aphthalene	nd	nd	nd	nd	nd	nd
henanthrène	nd	nd	nd	nd	nd	5.2
yrene	nd	nd	nd	nd	nd	5.2 5.5
Methylnaphthalene	nd	nd	nd	nd	nd I	a.a nd

NOTES:
Method 1 Standards from 310 CMR 40.0000
nd = compound not detected above method detection limit
'--' indicates analyte test not performed

TABLE 2. DETECTED CONCENTRATIONS IN GROUNDWATER SAMPLES SUPPLEMENTAL EXPLORATION PROGRAM: PLEASURE BAY STORM DRAIN

WELL ID:	REPORTABLE CONCENTRATIONS	FEDERAL SDWA	OW98-359	OW98-362	OW98-365 Pleasure Bay None Detected	
WELL LOCATION:			Pleasure Bay	Pleasure Bay		
/OLATILE ORGANICS (μg/L)			None Detected	None Detected		
VOLATILE PETROLEUM HYDROCARBONS (μg/L)				1		
C5-C8 Aliphatics (excludes BTEX and MTBE)	1,000	NL	< 100	< 100	< 100	
C9-C12 Aliphatics	1,000	NL	< 25	< 25	< 25	
C9-C10 Aromatics	4,000	NL	< 25	< 25	< 25	
Targeted VPH Analytes:	4,000	IAL	20	25	25	
Methyl-tert-butyl ether (MTBE)	50,000	A11				
	50,000	NL .	< 2	< 2	< 2	
Benzene	2,000	5	< 2	< 2	< 2	
Toluene	6,000	1,000	< 2	< 2	< 2	
Ethylbenzene	4,000	700	< 2	< 2	< 2	
m-&p-Xylenes	i		< 2	< 2	< 2	
o-Xylene ·	6.000	10.000	< 2	< 2	< 2	
Naphthalene	6,000	NL	< 2	< 2	< 2	
EXTRACTABLE PETROLEUM HYDROCARBONS (µg/L)					·	
C9-C18 Aliphatics	1,000	NL	J 210	< 110	< 110	
C19-C36 Aliphatics	20,000	NL NL		1 ''*		
C10-C22 Aromatics (excludes Targeted PAH Analytes)			180	< 110	190	
Forested DALL Applies argued PAR Analytes)	30,000	NL	300	< 110	130	
Fargeted PAH Analytes:						
Acenaphthene	5,000	NL	< 1.1	· < 1.1	< 1.1	
Acenaphthylene	3,000	NL	< 1.1	< 1.1	< 1.1	
Anthracene	600	NL	< 1.1	< 1.1	< 1.1	
Benzo(a)anthracene	3,000	NL	< 1.1	< 1.1	< 1.1	
Benzo(a)pyrene	3,000	0.2	< 1.1	< 1.1	< 1.1	
Benzo(b)fluoranthene	3,000	NL	< 1.1	< 1.1	< 1.1	
Benzo(g,h,i)perylene	3,000	NL NL	< 1.1			
Benzo(k)fluoranthene	3,000	NL NL		1		
			< 1.1	< 1.1	< 1.1	
Chrysene	3,000	NL	< 1.1	< 1.1	< 1.1	
Dibenz(a,h)anthracene	3,000	NL	< 1.1	< 1.1	< 1.1	
Fluorantherie	200	NL	< 1.1	< 1.1	< 1.1	
Fluorene	3,000	NL	< 1.1	< 1.1	< 1.1	
indeno(1,2,3-c,d)pyrene	3,000	NL	< 1.1	< 1.1	< 1.1	
Naphthalene	6.000	NL	< 1.1	< 1.1	< 1.1	
Phenanthrene	50	NL	< 1.1	< 1.1	< 1.1	
Pyrene	3,000	NL NL		\		
2-Methylnaphthalene	3,000	NL NL	\	< 1.1 < 1.1	< 1.1 < 1.1	
DISSOLVED PRIORITY POLLUTANT METALS						
PLUS BARIUM, IRON, AND MANGANESE (7) (µg/L)	1					
Antimony	- 1	_			_	
•	300	6	< 2.0	< 2.0	< 2.0	
Arsenic	400	50	13.02	< 2.4	< 2.4	
Barium	30,000	2,000	131	182	88.4	

TABLE 2. **DETECTED CONCENTRATIONS IN GROUNDWATER SAMPLES** SUPPLEMENTAL EXPLORATION PROGRAM: PLEASURE BAY STORM DRAIN

WELL ID: WELL LOCATION:		FEDERAL SDWA	OW98-359 Pleasure Bay		OW98-362 Pleasure Bay		OW98-365 Pleasure Bay			
Beryllium	50	4	<	0.40	7	0.30	<	0.30		
Cadmium	10	5	1	3.2	<j< td=""><td>2.2</td><td><j< td=""><td>2.2</td></j<></td></j<>	2.2	<j< td=""><td>2.2</td></j<>	2.2		
Chromium	2,000	100	<	7.8	<	3.3	<	3,3		
Copper	100,000	1,300 (5)	<	6.2	<	6.2	<	6.2		
Iron	NL	300 (4)		NA	1	NA		NA		
Lead	30	15	<j< td=""><td>0.84</td><td><j< td=""><td>0.84</td><td><j< td=""><td>0.84</td></j<></td></j<></td></j<>	0.84	<j< td=""><td>0.84</td><td><j< td=""><td>0.84</td></j<></td></j<>	0.84	<j< td=""><td>0.84</td></j<>	0.84		
Manganese	NL	50 (4)	1	NA	`	NA	•	NA		
Mercury	1	2	<	0.10	<	0.10	<	0.10		
Nickel	80	NL	<	8.5	<	8.5	1	8.6		
Selenium	80	50	<j< td=""><td>1.8</td><td> <j< td=""><td>1.8</td><td><j< td=""><td>9.0</td></j<></td></j<></td></j<>	1.8	<j< td=""><td>1.8</td><td><j< td=""><td>9.0</td></j<></td></j<>	1.8	<j< td=""><td>9.0</td></j<>	9.0		
Silver	7	100 (4)	1 2	3.5	<	3.5	13	3.6		
Thallium	400	2	<j< td=""><td>1.5</td><td><j< td=""><td>1.5</td><td><j< td=""><td>7.5</td></j<></td></j<></td></j<>	1.5	<j< td=""><td>1.5</td><td><j< td=""><td>7.5</td></j<></td></j<>	1.5	<j< td=""><td>7.5</td></j<>	7.5		
Zinc	900	5,000 (4)	<	28.0	<	28.0	, <	28.0		

NOTES:

- (1) Reportable Concentrations are from the MCP (MADEP, 1995 and revisions through 10/31/97).
- (2) Federal Safe Drinking Water Act Maximum Contaminant Levels. These values are included as an aid in evaluating the need for treatment of water generated from dewatering of excavations, prior to discharge to surface water. Such discharges are regulated under the National Pollutant Discharge Elimination System (NPDES). Although their use is not codified in regulation or specifically stated in policy, MCLs are generally used by EPA when stating NPDES permit limits for discharge to a water body.
- (3) MCL is for total trihalomethanes.
- (4) MCL for chloride, iron, manganese, silver, sulfate, total dissolved solids, and zinc is a secondary MCL (non-enforceable and established for aesthetic reasons).

- (4) MocL for chorder, from manganese, silver, surface, total dissolved solids, and zinc is a secondary MocL (non-enforceable and established for aestnet
 (5) Treatment technique. 90% of tap samples must meet this "no action" level for copper.
 (6) Samples were collected by EPA low-flow method and were NOT filtered in the field or in the laboratory before analysis.
 (7) Samples were collected by EPA low-flow method and were field-filtered before being bottled, preserved and submitted to the laboratory for analysis.
 The analyte was not detected at this concentration; value presented is the sample detection limit.
- Value is approximate due to limitations identified in the quality control review. Value rejected due to limitations identified in the quality control review.
- NA Not Analyzed or Not Applicable.
- ND None Detected
- NL No MCP Reportable Concentration or no SDWA MCL NR No Reading due to instrument malfunction
- - 2009 Concentration exceeds the GW2 reportable concentration.
 - 2.000 Concentration exceeds the federal SDWA MCL.